



LGS0410GLQ Standard Asphalt Distributor

LGS0410GLQ asphalt distributor is an economical type with compact structure and high working efficiency, which is mainly composed of truck chassis, asphalt tank, asphalt pumping and spraying system, heating system, hydraulic circuit, pneumatic circuit and operation panel. It can spray rubber asphalt, hot asphalt, emulsified asphalt, modified asphalt, etc.

Engine	
Model	ISDE 140
Type	Water-cooled, turbocharged, Tier III
Rated power	103KW
Rated speed	2200rpm
Main Technical Specification	
Chassis model	EQ1070T
Spray width	200-4500mm
Spray volume	0.5-2.0kg/m ²
Asphalt tank volume	4000L
Asphalt heater	Imported diesel oil burner
Spray media	Hot(modified)asphalt, diluted asphalt, emulsified asphalt, etc
Spray precision	±2°
N.V.W	7490kg
Payloading capacity	6000kg
G.V.W	13500kg
Axle loading capacity(F/R)	6000/8000kg
Max. traveling speed	90km/h
Approach angle	20°
Departure angle	12°
Transmission System	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Mechanical type	
Ratio	
Forward	9.01,5.24,3.22,2.20,1.50,1.00
Reverse	12.99
Axle And Type	
Front axle	DONGFENG
Rear axle	DONGFENG
Ratio	4.8
Tyre size	8.25-16
Steering System	
Hydraulic steering	
Clutch And Brake	
Single-plate dry coil-spring clutch, diameter 420	
Service brake	Air brake
Parking brake	Mechanical
Dimensions	
Overall length	6470mm
Overall width	2496mm
Overall height	2458mm
Wheel base	3800mm
Tread(F/R)	1835/1640mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572